



RDL60COB


- 92DL62040
- 92DL62027
- 92DL63040
- 92DL63027
- 92DL64040
- 92DL64027

RDL60COB



RDL60COB

| Catalogue number | Watt (W) | Whole fixture lumens (lm) | Colour temp. (K) | Colour body | Diameter (mm) | Height (mm) | Diameter 1 (mm) | Energy class |
|------------------|----------|---------------------------|------------------|-------------|---------------|-------------|-----------------|--------------|
| 92DL62040 | 20 | 1600 | 4000-4300 | white | 140 | 105 | 120 | A++A |
| 92DL62027 | 20 | 1600 | 2700-3000 | white | 140 | 110 | 120 | A++A |
| 92DL63040 | 30 | 2400 | 4000-4300 | white | 160 | 120 | 135 | A++A |
| 92DL63027 | 30 | 2400 | 2700-3000 | white | 160 | 110 | 140 | A++A |
| 92DL64040 | 35 | 2800 | 4000-4300 | white | 160 | 120 | 135 | A++A |
| 92DL64027 | 35 | 2800 | 2700-3000 | white | 160 | 110 | 140 | A++A |



Body: aluminium | Diffuser: glass | Light source: Epistar | Power factor: $\lambda > 0.9$ | Starting time: $< 0.5s$
LED recessed round downlight COB. Easy installation due to handy clips.



250

DOWNLIGHT