



COMERCIAL LED FIXTURES TRITON


Catalogue number	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Beam angle	Colour body	Length (mm)	Width (mm)	Height (mm)	Energy class
◆ 99TR602630/GR	26	2860	3000	90°	grey	600	90	57,6	A++A
◆ 99TR602640/GR	26	2860	4000	90°	grey	600	90	57,6	A++A
◆ 99TR602665/GR	26	2860	6500	90°	grey	600	90	57,6	A++A
◆ 99TR903830/GR	38	4180	3000	90°	grey	900	90	57,6	A++A
◆ 99TR903840/GR	38	4180	4000	90°	grey	900	90	57,6	A++A
◆ 99TR903865/GR	38	4180	6500	90°	grey	900	90	57,6	A++A
◆ 99TR1205030/GR	50	5500	3000	90°	grey	1200	90	57,6	A++A
◆ 99TR1205040/GR	50	5500	4000	90°	grey	1200	90	57,6	A++A
◆ 99TR1205065/GR	50	5500	6500	90°	grey	1200	90	57,6	A++A
◆ 99TR1506430/GR	64	7040	3000	90°	grey	1500	90	57,6	A++A
◆ 99TR1506440/GR	64	7040	4000	90°	grey	1500	90	57,6	A++A
◆ 99TR1506465/GR	64	7040	6500	90°	grey	1500	90	57,6	A++A



INSTALLATION ACCESSORIES FOR LED PROFILES

Suspension wire
Catalogue number: 99ACC54

As per personal request, COMERCIAL LED FIXTURES TRITON can be produced with beam angle of 30° and 60°



Body: aluminium | Reflector: polycarbonate (PC)

