



**DS1 - 125-160**



**DS1 - 250-800**



**DS1 MAX - 63-250**

### Remote control (electrical)

**5 YEARS GUARANTEE** \*for industrial usage, 3 years warranty

#### Description:

The device switches off/on the breaker to which manual operative rotary mechanism is mounted

- two operating positions of the executive mechanism fixed at 90°C

#### Mounting:

The base is mounted with bolts right on the cover (scheme 1 mounting), and the handle is mounted at the door of the distribution box, using an extension axis it is joined to the base

#### Electrical remote control for MCCB DS1

Type of the breaker	Dimensions (mm)					Packing/Box (pcs)	Catalogue number	
	A	A1	B	B1	H		Operating voltage (V) 230V	400V
DS1 125	103.5	110	30	90	92	1	<b>44912</b>	<b>44907</b>
DS1 160	103.5	110	35	90	92	1	<b>44913</b>	<b>44908</b>
DS1 250	139	-	132	-	105	1	<b>44914</b>	<b>44909</b>
DS1 400	226	-	132	-	132	1	<b>44915</b>	<b>44910</b>
DS1 630	226	-	132	-	132	1	<b>44916</b>	<b>44911</b>
DS1 800	226	-	132	-	132	1	<b>44916</b>	<b>44911</b>

#### Electrical remote control for MCCB DS1 MAX

Type of the breaker	Dimensions (mm)					Packing/Box (pcs)	Catalogue number	
	L1	B	B	H	H1		Operating voltage (V) 230V	400V
DS1 MAX 63A	116	90	50	77	12,5	1	<b>44917M</b>	<b>44906M</b>
DS1 MAX 125A	116	90	50	77	12,5	1	<b>44912M</b>	<b>44907M</b>
DS1 MAX 250A	116	90	70	77	15	1	<b>44914M</b>	<b>44909M</b>
DS1 MAX 400A	176	130	107	115	27	1	<b>44915M</b>	<b>44910M</b>
DS1 MAX 630/800A	176	130	119	115	31	1	<b>44916M</b>	<b>44911M</b>

