



Auxiliary contacts LT03-DN11

5 YEAR WARRANTY *for industrial usage, 3 years warranty


Providing on necessity additional number of plug points and are mounted sideward to the movable part of the magnetic cores of contactors of the series LT1 D. Variants with two additional plug points NO and NC are offered.

Functions:

- expanding the number of the operational plug points
- switching on simultaneously with the rest of the contact system
- of the contactor

Technical characteristics:

- Environment operational regime: AC 3
- Insulation voltage: 690V
- Double connector: screw connector
- Connection:
 - flexible conductors with or without cable end
 - solid conductors
- Mounting method:
 - mounting position – sideward to the contactor
- Plastic: resistant to UV and non-burning (self-extinguishing material)



Dimensions (mm)

W1	W2	H	L	A
73	48	22	12,5	72


Type	Rated current	Section of the conductor (mm ²)	Catalogue number
LT03-DN11	6A	0,5-1	23311



Time delay contact block LT02-Dxx

5 YEAR WARRANTY *for industrial usage, 3 years warranty

LT02-Dxx is designed to set time intervals from 0.1 to 180s in different control schemes. It is used most frequently in combination with contactors from LT1-Dxx series to form "star/delta" starters for electrical motor control, as it provides the necessary time for motor winding.



Dimensions (mm)

W	L1	h1	h2	H
33	48	22	14	59
W2				
45				

Type	Number of contacts	Time delay	Catalogue number
LT02-DT0	NO+NC	0.1~3s	23901
LT02-DT2	NO+NC	0.1~30s	23902
LT02-DT4	NO+NC	10~180s	23903